

# OPTIONS

#### **Flush Volume**

1.6 gpf (6.0 Lpf) (1.6) 1.28 gpf (4.8 Lpf) (1.28)

## Finish

Polished Chrome (CP) Polished Brass (PB) Brushed Nickel (BN) Brushed Stainless (SF) Graphite (GR)

# Water Efficiency

Low Consumption High Efficiency

## Handle

Front of Valve (H) Sanigard® (SG) Left of Valve (G) Nickel-Silver (YA) Right of Valve (I)

# **Push Button**

3" Metal Oscillating (L3) Metal Index (L) Front of Valve (HL3)

# **Control Stop**

1" Straight (E) Wheel Handle (K) Ground Joint (GJ) Less (L/STOP)

## Tailpiece

```
H551A 3 1/16" (H551A-3-1/16)
H551A 4 1/16" (H551A-4-1/16)
H551A 5 1/16" (H551A-5-1/16)
```

## Inlet

Back of Valve (B) Left of Valve (C)

# Vacuum Breaker

Less (XYV)

# Offset

1 <sup>1</sup>/<sub>2</sub>" (38mm) (1-1/2-OFST) 1" (25mm) (1-OFST)

## **Outlet Tube**

Trap Primer (TP)



Image for a standard ROYAL 111 shown

# DESCRIPTION

Royal® Exposed Manual Water Closet Flushometer

## FEATURES

- Water conservation is aided by the ADA-compliant, non-holdopen handle, which prevents toilet from exceeding intended flush volume
- Flush accuracy is controlled by CID<sup>™</sup> technology, also enhancing water efficiency
- Integrity of the product is maintained with the vandalresistant stop cap
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece
- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

## DOWNLOADS

- Royal Exposed Installation Instructions
- Control Stop Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide
- Tail Piece Repair and Maintenance Guide
- Royal Flushometers Repair and Maintenance Guide
- Flushometer Pressure gauges
- Additional Downloads

# SLOAN.

F189 (F189) F188 (F188)

#### Bumper

Angle Stop (YO) Angle Stop Extended (YG)

## **Pipe Support**

Solid Ring (YK)

#### **Special Features**

Less Logo (LL) Carbon Offset (CO) Whitworth Thread (WWT)

#### **Compliances & Certifications**

BAA Compliant cUPC Certified ADA Compliant Satisfies LEED Credits WaterSense Listed cUPC Green Certified BREEAM Water Credit Green Globes Water Credit LEED V4 Water Efficiency Credit LEED Materials & Resources EPD Credit

#### NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.

Sloan 10500 Seymour Ave, Franklin Park, IL 60131 Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

**PVD Special Finishes**